Searching PAJ

PATENT ABSTRACTS OF JAPAN

(11)Publication number:

04-178440

(43)Date of publication of application: 25.06,1992

(51)Int.Cl.

COBJ 9/04 COSK 7/22 COSL 63/00 B640 1/00 CO8L 63:00

(21)Application number: 02-306596

(71)Applicant:

NIPPON PETROCHEM CO LTD

(22)Date of filing:

(72)Inventor:

IWAI SAKUYA

SASAKI KOICHIRO

OSHIMA AKIO

(54) EPOXY RESIN COMPOSITION FOR FLAME-RETARDANT LIGHT-WEIGHT COMPOSITE MATERIAL, INTERMEDIATE AND COMPOSITE MATERIAL

(57)Abstract:

PURPOSE: To obtain a high-strength and lightweight composition for lightweight composite materials suitable for inner core materials, etc., being readily laminated, co-crosslinkable with other prepreg by blending an epoxy resin with specific amounts of fine hollow spheres, a blowing egent, a flame-retardant, etc.

CONSTITUTION: (A) 50-95 pts.wt. epoxy resin is blended with (B) 5-35 pts.wt. fine hollow spheres (e.g. glass or alumina silicate), (C) 0.1-15 pts.wt. blowing agent (e.g. azobisisobutyronitrile), (D) 5-30 pts.wt. flame-retardant (e.g. tetrabromobisphenol), (E) 0.5-10 pts.wt. curing agent (e.g. dicyan) and (F) 0.5-10 pts.wt. curing promoter. The composition is molded into a sheetlike or filmy state to give a single material intermediate for composite material, which is used to give composite materials or foamed and cured to give lightweight composite materials. Or a reinforced intermediate is obtained from the intermediate and a reinforcing material and processed to give lightweight composite materials or foamed and cured to give lightweight composite materials.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]